

AID LF RFID GLASS Transponder in Syringe AID LF ST01



**LF RFID transponder according ISO standard ISO 11784/11785 packed in Syringe
ICAR approved product code 900015**

Technology	FDX-B	Injectable glass tag	
Packaging	Glass tag in Syringe	Sterilized, sealed; with barcode label	
Physical spec. tag	Diameter:	2.12 mm	
	Length:	12mm	
	Material:	Bio Glass	
	Color	Transparent	
Electrical spec.	Operating Frequency:	134.2kHz (ISO FDX 11784 – 11785)	
ICAR product code	900015	ID code	To
Chemical parameters	Water immersion IP 68	26.000.000.000	26.000.999.999
	Resistant to mineral, alcohol, oil, 10% HCL and ammoniac		
Thermal spec.	Storage temp.	-40°C to +85 °C	
	Operating temp.	0°C to +50 °C	

Advanced ID Asia Engineering Co., Ltd. reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled.

Advanced ID Asia Engineering Co., Ltd. declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Advanced ID Asia Engineering Co., Ltd

65/12 M. 10 T. Tonpao A. Sankumpang Chiang Mai 50130, Thailand

Tel: +66 (0) 53 390910

Fax: + 66 (0) 53 390910

email: aae@aae.co.th

<http://www.aae.co.th>